

# DIGITUS Plug&View OptiVario

**DN-16039**  
**EAN 4016032336402**



**DIGITUS Plug&View OptiVario 2MP H.264 IP 11N Day&Night Varifocal Bullet camera**

The small DIGITUS® Plug&View OptiVario is a professional IP camera for rooms, halls and outdoor areas surveillance. The camera has optical zoom, to be set directly on the camera. Adapt your security camera directly to the monitored area. An included mounting kit supports a professional and simple installation. The IP66 enclosure ensures maximum weather protection and the camera's fast wireless LAN delivers smooth image and video quality to your smart phone/tablet or PC. With DIGITUS® Plug&View technology the installation of your OptiVario is done in 3 easy steps. Everything just works with DIGITUS® Plug&View.

**Your wireless outdoor Plug&View IP camera with IP66 housing and optical zoom**

- 2 megapixel video resolution (UXGA 1600 x 1200, HD720 1280 x 720)
- 2 megapixel video resolution (Full HD 1920 x 1080, HD720 1280 x 720) Rev.2
- Video stream with low latency and network load thanks to H.264 compression format
- Powerful, mobile surveillance with support for iOS and Android devices
- Wi-Fi in accordance with the latest 11n standard for seamless transmission
- IP66 housing design for outdoor use
- Suitable for all common browsers
- Simple and quick installation with P2P support and QR code scanning
- Built-in infrared LEDs and infrared cut-off filters for day and night monitoring

- LAN speed: 10/100Base-TX Ethernet
- Supports up to 25fps video frame rate at HD720 and 15fps at UXGA
- Supports up to 25fps video frame rate at HD720 and 15fps at Full HD (Rev.2)
- Integrated 2 GB storage for recording videos and snapshots
- Powerful motion detection – automatically records and saves (motion) images via e-mail/FTP server
- Easy mounting with supplied fittings
- Operating temperature -20 to +50 °C
- Power source (±10 %): DC12 V / 1 A
- PoE - Power over Ethernet (Mode A)
- Dimensions (mm): 90(L) x 70(W) x 235 (H)
- Supports the DIGITUS® Plug&View app for smartphones and tablets
- Optical zoom lens: F1.4 / 2.8-12 mm
- Adjustable horizontal viewing angle: 20° - 65°
- WPS (Wireless Protected Setup) function provides fast, easy, and secure wireless encryption (Rev.2)
- WPS (Wireless Protected Setup) function provides fast, easy, and secure wireless encryption (Rev.2)
- Minimum Internet requirements: DSL 1000 (1,024 kbps download/384 kbps upload)
- Minimum requirements for smartphone access: 3G network connection

**Package contents**

- IP camera
- Product support CD-ROM
- Patch cable
- Mounting kit
- Power Supply

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	12	15.80	37.50	30.00	48.35	54,393.80
Packaging Unit Inside	1	1.32	27.50	11.50	11.50	3,636.88
Packaging Unit Single	1	1.32	27.50	11.50	11.50	3,636.88
Net single without Packaging	1	0.96	27.50	11.50	11.50	3,636.88

More images:

